

Additel 914A Handheld Pneumatic Pressure Test Pump

- Generate 95% vacuum to 375 psi (25 bar) pressure
- Portable, only 3.3 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors





Generated Pressure Range: 95% vacuum to 375 psi (25

Seals: Buna-N, PTFE, Copper Alloy

Hand-tight connectors for both test gauge and

1/4NPT female, 1/2NPT female, 1/4BSP female,

OVERVIEW

The 914A Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 95% vacuum to 375 psi (25 bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 914A is an ideal comparison test pump for pressure instruments calibration.

SPECIFICATIONS

bar) positive pressure

Material: Ram/adapters: SS

Piston volume: 21 ml (1.3 in³)

Height: 5.12" (130 mm)

Weight: 3.3 lb (1.5 kg). Warranty: 1 year

Adjustment Resolution: 10 Pa (0.1 mbar).

Body: SS, aluminum

1/2BSP female, or M20X1.5 female

Base: 9.45" (240 mm) x 4.72" (120 mm)

Media: Air.

Connection

Dimensions

reference gauge.

FEATURES

Portable:

- Only 3.3 lb (1.5 kg)
- Adjustment Resolution 10 Pa (0.1 mbar) High-quality screw press for fine pressure adjustment
- Great Stability
 - A specially designed shut-off valve makes the pressure as stable as possible during calibration
- Durable and Minimal Maintenance Built-in gas-liquid isolator protects the pump from moisture and dirt
- Easy-to-use
- Hand-tight Quick Connectors

Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches

ORDERING INFORMATION

Model Number

Manual: 1 pc

Model Number	
ADT914A — N • •	SET
	T
Model	
Pressure port type: N -1/4NPT female N2 - 1/2NPT female B - 1/4BSP female B2 - 1/2BSP female M-M20X1.5 female	SET: Pump and carrying case included
Accessories included O-ring: 20 pcs	

Optional Accessories

Model number	Description
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs).
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs).
ADT100-HTK-8K	Hose test kit, 5 feet flexible hose, 8,000 psi, user selectable male (1/4NPT, 1/2NPT, 1/4BSP, 1/2BSP, M20) to user selectable female hand tight quick connector.
9901-914	Carrying Case for one 914A pump and two 681 gauges or 672 calibrators
ADT914A-MK	Maintenance kit for Additel 914A pump

Note: For oil free applications contact Additel.

Carrying case (914A-X-SET models only)

