



# DPI 800/802

## Druck pressure indicator/loop calibrator

### Features

- Ranges from 25 mbar to 700 bar (10 in H<sub>2</sub>O to 10,000 psi)
- Single or dual range configuration
- mA measure, switch test and 24V loop power
- Large backlit display, menu driven interface
- HART® loop resistor
- Robust and weatherproof
- Compact, simple to use, easy to carry
- Convenient, one-handed operation
- Secure grip, impact resistant, elastomer protected
- Plug and play IUPM/IUPMP (IDOS) universal pressure modules provide accuracies to 0.05% FS all inclusive or 0.01% precision

### Applications

- Pressure test and maintenance
- Transmitter calibration
- Loop set-up and diagnostics
- Switch verification

The DPI 800 Series provides a complete range of advanced, robust and simple to use hand-held instruments. Highly cost effective, these tools are ideal for test/calibration of many popular process parameters. Advanced features address more applications in less time and deliver results you can rely on.

# DPI 800/802 specifications

	DPI 800	DPI 802	DPI880
Type	P	P	P
Indicator (measure pressure)	✓	✓	✓
Calibrator (measure or source)			✓
Thermometer (dual input T1, T2, T1 – T2)			✓
<b>Dual capability</b>			
mA measure with 24 V loop power		✓	✓
Switch test		✓	✓
HART resistor		✓	✓
IUPM/IUPMP (IDOS) pressure modules	❶	❶	❶
<b>Features</b>			
Programmable step and ramp output			✓
Hold, scaling, max/min/avg, filter, alarm, tare	✓	✓	✓
25 pressure units, flow scaling, leak test	✓	✓	✓
1000 point data memory, RS232	❸	❸	❸
<b>Applications</b>			
Measurement and monitoring	✓	✓	✓
Indicator, controller and recorder testing	✓	✓	✓
Transmitter maintenance and calibration		✓	✓
Process loop set-up and maintenance		✓	✓
Switch, trip and safety system testing		✓	✓

❶ Optional (please refer to IUPM/IUPMP (IDOS) pressure modules datasheet), ❷ When fitted with IUPM/IUPMP pressure module, ❸ Optional (please refer to accessories IO800E).

## Pressure test and measurement

### DPI 800 pressure indicator

The ideal tool for pressure test and measurement

### Pressure ranges

25 mbar to 700 bar (10 in H<sub>2</sub>O to 10,000 psi) including vacuum options

### All-inclusive accuracy

Can be relied on from one year to the next, even in tough environmental conditions (see specifications)

### Dual sensor configuration

Extended measurement range and simultaneous two channel reading (P1 and P2 or P1 – P2)

### Stainless steel sensor construction

Available for compatibility with a wide range of fluids and gases (refer to pressure range table)

### Programmable leak test

Reports the pressure drop and leak rate

### Advanced features

Hold, maximum/minimum/average, alarm, and tare facilitate troubleshooting

## Pressure instrument and loop maintenance

### DPI 802 pressure loop calibrator

Provides simultaneous pressure and mA measurement for transmitter and loop maintenance

### Dual readings

Simultaneous measurement of pressure and mA for transmitter calibration and loop maintenance

### 24V loop power supply



Energizes transmitters and control loops

### Automatic switch test

Captures open/closed trip values providing a fast and highly accurate “safety system” check

### HART resistor

Can be switched into the loop when required by a HART digital communicator and avoids the inconvenience of carrying a 250 Ω resistor



# DPI 800/802 specifications

## Universal plug and play pressure modules

### Intelligent Digital Output Sensor (IDOS)

Universal Pressure Modules are available from 25 mbar to 700 bar (10 in H<sub>2</sub>O to 10,000 psi).

#### Total flexibility

IUPM/IUPMP pressure modules can be used with any compatible instrument; for example, a DPI880 can become a fully featured pressure calibrator.

#### Plug and play

Modules are interchangeable between instruments, requiring no set-up or instrument calibration.

#### Range expansion

Achieved by adding IUPM/IUPMP pressure modules (please refer to the Universal Pressure Modules datasheet).

## Pressure Range Table

Pressure range	G/D	G	A	Media		*Accuracy %FS	
				+	-	Standard (S)	Premium (P)
25 mbar (±10 in H <sub>2</sub> O)	✓			②	③	0.1	0.03
70, 200, 350, or 700 mbar (±1, 3, 5, or 10 psi)	✓			②	③	0.075	0.03
350 mbar (5 psi)			✓	②		0.1	N/A
-1 to 1 or 2 bar (-15 to 15 or 30 psi)	✓			②	③	0.05	0.01
2 bar (30 psi)			✓	②		0.075	N/A
-1 to 3.5, 7, 10 or 20 bar (-15 to 50, 100, 150 or 300 psi)		✓		①		0.05	0.01
7, 20 bar (100, 300 psi)			✓	①		0.075	N/A
35, 70, 100, 135, 200 bar (500, 1000, 1500, 2000 or 3000 psi)		✓		①		0.05	0.01
350 or 700 bar (5000 or 10,000 psi) sealed gauge		✓		①		0.05	N/A

G = gauge, A = absolute, G/D = gauge/differential; calibrated referenced to atmosphere maximum line pressure 2 bar (30 psi). ① Stainless steel, compatibility ② Non-corrosive gas/fluid and ③ Non-corrosive gas. (N/A = not available). Accuracy assumes regular zero correction.

### \*S-Standard accuracy

Total accuracy over 0°C to 50°C (32°F to 122°F), including one year stability and calibration uncertainty

### \*P-Premium accuracy

- Precision over 18°C to 28°C (65°F to 82°F)
- For operation over 5°C to 45°C (41°F to 113°F):  
0.014% FS for ranges above 700 mbar (10 psi)  
0.075% FS for ranges below 1 bar (15 psi)
- Stability over a year:  
0.01% reading ranges above 350 mbar (5 psi)  
0.03% reading ranges below 700 mbar (10 psi)
- Calibration uncertainty: 50 ppm of reading

### Single or dual range

One or two internal sensors can be selected. For dual range instruments, G/D ranges will be configured as G (gauge).

Only one of the two sensors can be 100 bar (1500 psi) or above.

Overpressure (maximum transient/intermittent pressure)

- 350 mbar (5 psi) and below 4 x FS
- 700 mbar to 700 bar (10 to 10,000 psi) 2 x FS
- Maximum working pressure: 1.1 x FS

### Pressure connections

G 1/8 female or 1/8 NPT female

### DPI 802 only

Measure	Accuracy
0 to 55.000 mA	0.02% reading + 3 counts
Temperature coefficient	-10°C to 10°C, 30°C to 50°C, 0.002% FS/°C (14°F to 50°F, 86°F to 122°F, 0.0011% FS/°F)
Switch detection	Open and closed. 2 mA current
Loop power output	24 V ±10% (35 mA maximum)
HART mA loop resistor	250 Ω (menu selection)
Electrical connectors	4 mm sockets

## DPI 800 series common specification

### Operating temperature

-10°C to 50°C (14°F to 122°F)

### Storage temperature

-20°C to 70°C (-4°F to 158°F)

# DPI 800/802 specifications

## Humidity

0% to 90% non-condensing

## Shock and vibration

BS EN61010

Def Stan 66-31, 8.4 Cat III

## EMC

BS EN61326-1

## Electrical Safety

EN 61010-1

## Pressure Safety

Pressure Equipment Directive – Class: Sound Engineering Practice (SEP)

## Approvals

CE marked

## Display

Graphic LCD with backlight. Resolution 99999

## Size (l x w x h)

180 mm x 85 mm x 50 mm (7.1 in x 3.3 in x 2 in)

## Weight

500 g (18 oz)

## Batteries

3 AA alkaline, >50 hours measure, >10 hours 24V source

## Accessories

### IO800A

Soft fabric carrying case with accessory pocket

### IO800B

Belt clip, wrist strap/hanging loop and bench stand

### IO800E

Data logging upgrade and RS232 lead:

**Log data** periodically (1s to 23h 59m 59s) or manually by key press.

**Review data** on-screen or upload to a PC via the RS232 interface. No software purchase is necessary as standard Microsoft® applications provide data transfer (HyperTerminal) and analysis (Excel). Alternatively, print directly to a compatible serial printer.

**Real time clock** with date.

**Memory:** 1000 single or 750 dual reading screens with date and time.

**Header tag:** 6 user characters to identify groups of readings.

**RS232:** 19200 baud, 8 data bits, 1 stop bit, no parity, Xon/Xoff.

**Data output:** comma separated ASCII.

## Ordering information

Each unit is supplied with batteries, calibration certificate and user guide. The DPI 802 series include a set of electrical test leads.

### 1. Model Type:

**DPI800S** Standard Accuracy Single Range

**DPI800D** Standard Accuracy Dual Range

**DPI802S** Standard Accuracy Single Range

**DPI802D** Standard Accuracy Dual Range

**DPI800PS** Premium Accuracy Single Range

**DPI800PD** Premium Accuracy Dual Range

**DPI802PS** Premium Accuracy Single Range

**DPI802PD** Premium Accuracy Dual Range

### 2. Pressure range(s) G, A or G/D and calibration unit

(Refer to Page 3 – pressure range table)

### 3. Calibration unit

- Bar
- psi
- hPa
- kPa
- inH<sub>2</sub>O
- mbar
- MPa

### 4. Pressure connection

**BSP** – G1/8 BSP female

**NPT** – 1/8 NPT female

### 5. Instrument set up

- UK and Europe
- USA
- Japan
- Russia
- Other Countries

*Note: Other countries to be configured as UK and Europe.*

### UKAS Calibration

We also offer UKAS accredited calibrations, please advise at the time of order placement if required.

### Accessories

Please state any accessories required as separate items when placing order.

## Related products

Druck is a world leader in the design and manufacture of pressure, temperature and electrical field calibrators, laboratory/workshop calibration equipment and pressure sensors.

## Supporting services

Our highly trained staff can support you, no matter where you are in the world. We can provide training, nationally accredited calibration – both initially and at periodic intervals – extended warranty terms, maintenance and even rental of portable or laboratory calibrators. Further details can be found at

[Druck.com/Services](http://Druck.com/Services)

*Distributed by:*

**Eurotron Instruments Benelux B.V.**

Vossenkamp 7a

9351 VR Leek, The Netherlands

Tel: +31 594 696 131

E-mail: [info@eurotronbenelux.nl](mailto:info@eurotronbenelux.nl)

Web: [www.eurotronbenelux.nl](http://www.eurotronbenelux.nl)

Delivering world class  
pressure measurement  
and calibration technology



Copyright 2024 Baker Hughes Company. All rights reserved.

920-110E

(09/2024)

BHCS38749A

**Baker Hughes**

**eurotron**  
instruments NL